

UT-IND-2Act

DATASHEET

***HIGH PERFORMANCE CARRIER WiFi
OPTIMIZED Indoor AP***

☼ Concurrent Dual Band

☼ High Performance

☼ 2x2 MIMO 802.11ac

☼ Up To 1.2Gb

☼ Multiple SSID

☼ Easy To Deploy

☼ Fast Roaming



TECHNICAL SPECIFICATION

WIRELESS

WLAN standard	IEEE 802.11 a/b/g/n/ac
Radio Mode	Dual Band MIMO 2x2
Operating Mode	Access point, routing, bridge
Radio Frequency Band, Data Rates and Channel Size	2.402 — 2.484 GHz (country dependent) up to 300Mbps 5/10/20/40 MHz 5.170 — 5.875 GHz (country dependent) up to 866.7Mbps 20/40/80 MHz
Wireless Security	Multiple options — Open system, WEP, WPA-PSK, WPA-PSK2, WPA-EAP, WPA-EAP-SIM/AKA
Roaming	IEEE 802.11r

ANTENNA

Type	4xOmni-directional: 2.4GHz — 3dBi, 5.8GHz — 3dBi
Mounting Possibilities	Table / Wall / Ceiling

CONNECTIVITY

Ethernet	2 x 1000 BaseT, RJ-45 ports (1xWAN + 1LAN or 2xLAN)
----------	---

NETWORKING

VLAN	Ethernet / Wireless side 802.1Q server / client / passthrough with switching
IP Support	IPv4 and IPv6
Routing	Static (RIP v2 / OSPF / BGP)
Firewall	Supported IPv4 & IPv6, User defined zones (WAN, LAN, DMZ) Masquerading, DNAT/SNAT
QoS	Supported
Tunneling	IP-IP / IP-IPv6 / IPv6-IP / IPv6— IPv6 / GRE / IPSEC
Logical Interfaces	PPP / PPPoE / PPTP / L2TP
DNS Service	Static / Caching / Filtering / Dynamic DNS
DHCP Service	Configurable IPv4 / IPv6 on Ethernet
Management	WebUI, CLI, SNMP v2 and v3, remote syslog server support TR069, NMS agent
Power and Consumption	IEEE 802.3at PoE (48VDC) or DC 12V/1.5A
Temperature and Humidity (non-condensing)	- 20°C to 60°C, 0% ~ 85% Typical